

LA400PKGUL

# 24VDC RESIDENTIAL LINEAR ACTUATOR

Our most popular swing gate operator for residential applications.

PRODUCT HIGHLIGHTS

**BATTERY BACKUP**  
**myQ® TECHNOLOGY**  
 Allows You to Securely Monitor and Control Your Gate Operator from Anywhere with the myQ App



## RELIABLE

**COMMERCIAL-DUTY CAST-ALUMINUM HOUSING** WITH HEAVY-DUTY DC MOTOR PERFORMS IN THE MOST DEMANDING APPLICATIONS.

**SMOOTH START/STOP OPERATION** AND MID-TRAVEL REVERSAL EXTEND HARDWARE LIFE OF THE GATE AND OPERATOR.

**BATTERY BACKUP** PROVIDES SEAMLESS ACCESS BY PROVIDING STANDBY POWER WHEN THE POWER IS DOWN.

**SURGE SUPPRESSION** PROVIDES INDUSTRIAL SURGE AND LIGHTNING PROTECTION AGAINST STRIKES UP TO 50 FEET AWAY.

**WARRANTY** 2 YEARS.

## SMART

**myQ TECHNOLOGY** ENABLES YOU TO SECURELY CONTROL AND MONITOR YOUR GATE OPERATOR FROM ANYWHERE.\*

**WIRELESS DUAL-GATE COMMUNICATION** SYNCHRONIZES GATE OPENING/CLOSING AND ELIMINATES EXPENSIVE DRIVEWAY TRENCHING COSTS (REQUIRES SECOND CONTROL BOX).

**BI-PART DELAY** MONITORS AND ADJUSTS SPEED AND POSITION OF EACH WING TO ENSURE PRIMARY GATE CLOSES LAST.

**PARTY PASS** ALLOWS FOR THE GATES TO BE HELD OPEN FOR AN EXTENDED PERIOD OF TIME.

**SOLAR-READY, ULTRA-RELIABLE SYSTEM** DELIVERS POWER WHEN AND WHERE YOU NEED IT MOST.

## SAFE AND SECURE

**SECURITY+ 2.0®** SAFEGUARDS FACILITY ACCESS WITH ROLLING CODE TECHNOLOGY, OPENING FOR REGISTERED DEVICES ONLY.

**INHERENT REVERSING SENSOR** DETECTS OBSTRUCTIONS AND REVERSES GATE WHEN CLOSING OR STOPS/REVERSES THE GATE WHEN OPENING.

**FIRE DEPARTMENT COMPLIANCE** ALLOWS GATE TO AUTO-OPEN UPON LOSS OF AC POWER OR BATTERY DEPLETION.

**MANUAL DISCONNECT** WHEN UNLOCKED ALLOWS GATE TO BE OPENED MANUALLY.

**UL® LISTED** GATE OPERATORS WITH MONITORED SAFETY ENTRAPMENT PROTECTION DEVICES.

\*Cellular data or Wi-Fi® connection required. Test equipment regularly and follow safety instructions.

### INCLUDED ACCESSORIES:

**MONITORED RETRO-REFLECTIVE PHOTO EYE**  
 Enhanced retro-reflective photo eye now with heater and wider beam, engineered to stay aligned; max. range: 50 ft.



LMRRL

### SAFETY ADD-ONS:

**MONITORED THROUGH-BEAM PHOTO EYES**  
 Enhanced through-beam now with wider beam and heater for high performance in most environments; max. range: 90 ft.



LMTBL

**MONITORED WIRELESS EDGE KIT**  
 Low-energy Bluetooth® connection between a LiftMaster Monitored Resistive Edge and the gate operator; max. range: 130 ft.\*\*



LMWEKITU

**MONITORED SAFETY ENTRAPMENT EDGES**  
 Full line of Small, Large and Wraparound Profile Edges that sense obstructions.



EDGES

### TOTAL SOLUTION ACCESSORIES:

**WIRELESS COMMERCIAL KEYPAD**  
 Provides constant pressure override to control gate operator if safety devices fault yet are free of obstructions. Hold Open/Party Pass enabled with gate operator firmware 4.2 or higher.



KPW5

**INTERNET GATEWAY**  
 Connects myQ-enabled gate operators to the Internet and enables control through the myQ App.



828LM

**SOLAR PANEL KIT**  
 Uses the sun to power the operator with (2) 10W or (2) 20W solar panels.



210W/220W

\*\*Wireless kit for up to 4 transmitters and 2 resistive edges per transmitter.

## MASTERFUL ENGINEERING.

## MECHANICS



- 24VDC Continuous-Duty Motor
- **Operator Duty Rating:** 100 Cycles per Day
- **Wormgear Reduction:** Precision-Machined All-Metal Gear Drive

## POWER



- 115 Single-Phase (Standard Control Box)
- **Solar-Ready, Ultra-Reliable System** Delivers Power When and Where You Need It (LMRRUL/LMTBUL Heater Option Not Recommended for Solar Applications)
- **Accessory Power:** 24VDC 500mA Output

## COMMERCIAL-GRADE DESIGN



- **Housing:** Commercial-Duty Cast Aluminum
- **UL® Usage Classification:** I, II, III and IV
- **Weights:**  
Actuator Arm: 19 lbs.  
Standard Control Box: 13 lbs.  
(Includes [2] 7Ah Batteries)

## RECOMMENDED CAPACITIES



16.41"

6.65"

14.44"

6.06"

37.96"

3.93"



LA400CONTUL




LA400DC

XLSOLARCONTUL  
[NOT INCLUDED]

21.00" x 17.22" x 6.19"

## TEMPERATURE SPECIFICATIONS

-4°F (-20°C) to 140°F (60°C)

**GATE TRAVEL SPEED**  
Opens 90° in 15–17 Seconds

## STANDARD FEATURES.

## SYNCHRONIZED CLOSE

- Simultaneously Closes Gates

## MONITORED SAFETY INPUTS

- 3 Main Board, 3 Optional Expansion Board

## SECURITY+ 2.0® ON-BOARD RADIO RECEIVER

- Up to 50 Remote Controls  
(Unlimited with 811LMX/813LMX)

## LED DIAGNOSTIC DISPLAY

- Simplifies Installation and Troubleshooting

## HOMELINK® COMPATIBLE

- Version 4.0 or Higher\*



\*May require an external adapter depending on the model and year of your vehicle. Visit [HomeLink.com](http://HomeLink.com) for additional information.

WITH OPTIONAL  
EXPANSION BOARD ONLY

## QUICK CLOSE

- Closes the Gate Immediately After a Vehicle Pulls Off the Interrupt Loop

## ANTI-TAILGATE

- Prevents Unauthorized Access

## SUPPORT.



For Support Tools and Training Videos, Visit  
[LiftMasterTraining.com](http://LiftMasterTraining.com)

For More Information on Gate Operators, Visit  
[LiftMaster.com/UL325Gates](http://LiftMaster.com/UL325Gates)

To Find the Right Perimeter Access Solution  
for You, Visit  
[LiftMaster.com/Solution-Generator](http://LiftMaster.com/Solution-Generator)



Sales Support: 800.282.6225  
Technical Support Center: 800.528.2806  
To Order: 800.323.2276